



MACHINE CONSTRUCTION
AGRICULTURE IRRIGATION EARTH MOVING

AP ATTACHMENT GRADER TWISTER



Technical specifications

Type	Twister I	Twister II	Twister III
Machine overall			
Overall length [mm]	2110	2500	2500
Overall height [mm]	1100	1300	1300
Wheel base [mm]	1000	1200	1200
Angle turntable°	25 left / 25 right	30 left / 30 right	30 left / 30 right
Blade length [mm]	1600 / 1800	2000 / 2200 / 2400	2400 / 2600 / 2800
Blade height [mm]	400	450	450
Knife height/thickness [mm]	100 x 16	100 x 16	100 x 16
Technical specifications cylinders			
Side-shift range [mm]	+ 300 / - 300	+ 400 / - 400	+ 400 / - 400
Pitch range°	-5 / 0 / 5 / 10	-10 / -5 / 0 / 5 / 10	-10 / -5 / 0 / 5 / 10
Elevation range [mm]	285	300	300
Technical requirements			
Gross weight wheelloader	< 1800 kg	1500-3600 kg	3200-5500 kg



MACHINE CONSTRUCTION

AGRICULTURE IRRIGATION EARTH MOVING

AP ATTACHMENT GRADER TWISTER



Mechanically adjustable in 4 positions : -5°/0°/5°/10°

The AP graders can be equipped with complete grader control

